

IC-215P-AA2

21.5" PCAP Touch Computer




Stand sold separately
Part #SS-156-A1

Description

The IC-215P-AA2 equipped with Rockchip's latest architecture, the RK3399 combining low power consumption and high-performance computing into one integrated PC. The CPU's performance combined with the ultra-slim aesthetic of this AiO works well in any environment. Loaded with the latest Android OS, 9.0 and Google Mobile Services, for easy plug-n-play functionality creates the opportunity for your team to easily incorporate this model into a new or existing application. From POS to an exposed kiosk, self-service to point of information, this product offers peripherals to support – MSR and Camera Module Kit, a wide range of applications, making it a perfect form – fit – function solution for a variety of applications.

Featured Specifications

- Size: 21.5 " TFT LCD
- Processor: Rockchip RK-3399, Dual-core Cortex-A72 up to 1.8GHz, Quad-core Cortex-A53 up to 1.4GHz
- Maximum Resolution: 1920 x 1080
- Contrast Ratio: 1000:1
- Aspect Ratio: 16:9
- Brightness: 250 nits (No Touch), 225 nits (P-CAP)
- View Angle: H: 178°, V: 178°
- Video Port: 1 x HDMI, 1 x 3.0 Type A, 1 x 3.0 USB Type C (OTG support)
- Warranty: 3 year



Specifications

System Configuration

Processor	Rockchip RK-3399, Dual-core Cortex-A72 up to 1.8GHz, Quad-core Cortex-A53 up to 1.4GHz
GPU	Mali-T860 MP4
System Memory	4GB LPDDR4
Storage Device	32GB eMMC
Wi-Fi & Bluetooth	802.11 a/b/g/n/ac, Bluetooth 4.0 (Support BLE)
GPS	Enabled

Touch LCD Display

Size / Resolution	21.5" TFT LCD / 1920 x 1080
Touch Screen	Projected Capacitive Touch, 10 Points
Brightness (Touch Type)	250 nits (No Touch), 212 nits (P-CAP)
Contrast Ratio	3000:1
View Angle	H: 178°, V: 178°
Display Surface	7H Hardness durable glass

I/O Ports

USB Port	1 x USB 3.0 Type A, 1 x USB 3.0 Type C OTG (Supports DP 1.2 4-lane)
LAN Port	1 x LAN (10/100/1000Mbps)
Video Port	1 x HDMI (1080p 60Hz support)
Audio Port	1 x Built-In Microphone
Power Input	1 x 12v DC
SD Slot	1 x Micro SD Slot (SDHC 2.0 support)

Operating System Support

OS	Android 9.0 with Google Mobile Services
----	---

Physical Properties

Power Supply	Max. 60W (12V, 5A) External Power Adaptor
Speaker	2 x 2W
Material	Plastic, Glass, SECC Metal
Housing Color	Dark Gray
Dimensions (W x H x D) mm	510.96mm x 308.01mm x 37.9mm
Net Weight (kg)	4.0kg
Gross Weight (kg)	6.2kg
Carton (W x H x D) mm	610mm x 405mm x 160mm

Specifications (continued)

VESA	100mm x 100mm
------	---------------

Safety

Certifications	CE, FCC, LVD, UL, RoHS
----------------	------------------------

Environment

Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH. Non-Condensing

Optional Peripheral

MSR	MSR-215-A1 (Sold Separately)
Camera	CAM-000-A1 (Sold Separately)
21.5" Slim Stand	SS-215-A1 (Sold Separately)



www.MicroTouch.com | us.orders@microtouch.com

MicroTouch Interactive, Inc.
200 East Broadway Avenue, Maryville, TN 37804 | (616) 786-5353

The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by MicroTouch Interactive, Inc. standard terms and conditions of sale. Products are subject to availability. Copyright © 2025 MicroTouch Interactive, Inc. All rights reserved. MT21-1012 - 032425