

OF-320P-A1

32" PCAP Touch Monitor






Description

The OF-320P-A1 is a 32" Full HD (1920 x 1080) PCAP, 30-point touch solution—encouraging effective and efficient user collaboration and engagement for many environments. The ultra slim build coupled with input/output versatility, a 20 mm slim bezel design and high contrast showcases its ability to exceed all your aesthetic and performance requirements. From collaborative settings to an embedded application for a point-of-service kiosk, wayfinding, or content sharing—the OF-320P-A1 delivers everything desired in a large format touchscreen.

Featured Specifications

- Size: 31.5" TFT LCD
- Maximum Resolution: 1920 x 1080
- Contrast Ratio: 3000:1
- Aspect Ratio: 16:9
- Brightness: 500 nits (No Touch), 450 nits (P-CAP)
- View Angle: H: 178°, V: 178°
- Video Port: 1 x VGA, 1 x DP, 1 x HDMI 1.3
- Warranty: 3 year



Specifications

Touch LCD Display	
Touch Screen	Projected Capacitive
Touch Points	30
Touch Screen Interface	USB-HID (Type B)
I/O Ports	
Serial Port	-
USB Port	1 x USB 2.0 (Type B) for Touch Interface (USB-HID)
Video Port	1 x VGA, 1 x DP, 1 x HDMI 1.3
Audio Port	-
Power Input	1 x AC Power Input
Physical Properties	
Power Supply	AC Input 100~240VAC, 50~60Hz
Speaker	-
Housing Color	Black
Construction	Glass, SECC Metal
Compliance	Front Panel IP65 Compliant
Dimensions (W x H x D) mm	739.4 x 433.85 x 61
Net Weight (kg)	10.4
Gross Weight (kg)	13.5
Carton (W x H x D) mm	890 x 155 x 630 mm
VESA	200 x 200 mm
Ball Drop	IK08
Safety	
Certifications	CE, FCC, UL/CUL, CCC, RoHS
Environment	
Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 20% ~ 90% RH. Non-Condensing
Optional Peripheral	
Remote Key	-



www.MicroTouch.com | us.orders@microtouch.com

MicroTouch Interactive, Inc.