

SK-190P-A1

19" PCAP 3-in-1 Touch Monitor





Stand sold separately
Part #IS-000-A1

Description

The SK-190P-A1 is a 19" standard format convertible monitor perfect for any industrial grade application, embedded or exposed, that requires quality and reliability in high use environments. Versatile by design, this 19" monitor fits a variety of applications with the ability to withstand harsh conditions while retaining high performance levels. The IP65 rating coupled with an updated I/O selection for seamless integration and OSD controls built into the back housing create a user experience that is effortless and simplistic.

Featured Specifications

• Size: 19" TFT LCD

Maximum Resolution: 1280 x 1024

• Contrast Ratio: 1000:1


• Aspect Ratio: 5:4

Brightness: 250 nits (No Touch),
 225 nits (P-CAP)

• View Angle: H: 170°, V: 160°

• Video Port: 1 x VGA (DB15), 1 x HDMI, 1x DP

· Warranty: 3 year



Specifications

Touch Screen	Projected Capacitive
Touch Points	10
Touch Screen Interface	USB-HID (Type B)
	· // /
I/O Ports	
Serial Port	l x RJ11 Remote OSD
USB Port	1 x USB 2.0 (Type B) for Touch Interface
Video Port	1 x VGA (DB15), 1 x HDMI, 1x DP
Audio Port	-
Power Input	1 x 2.1 mm 12V DC Jack
Physical Properties	
Power Supply	Max. 60W (12V, 5A) External Power Adaptor
Speaker	-
Housing Color	Black
Construction	Glass, SECC Metal, Plastic (ABS)
Compliance	Front Panel IP65 Compliant, Rear IPX1
Dimensions (W x H x D) mm	416 x 344 x 46.6 mm
Net Weight (kg)	4.4 kg
Gross Weight (kg)	6.3 kg
Carton (W x H x D) mm	500 x 425 x 133 mm
VESA	100 x 100 mm
Ball Drop	-
Safety	
Certifications	CE/FCC/UL(62368)/CB (62368)/CCC
Environment	
Operating Temperature	0° C ~ 40° C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20° C ~ 60° C, 10% ~ 90% RH. Non-Condensing
Optional Peripheral	
Industrial Stand	IS-000-A1 (Sold Separately)
Remote OSD	Rem45-A1 (Sold Separately)



www.MicroTouch.com | us.orders@microtouch.com

MicroTouch Interactive, Inc.