

SK-215P-A1

21.5" PCAP 3-in-1 Touch Monitor



Stand sold separately
Part #IS-000-A1

Description

The commercial-grade, SK-215P-A1, is a Full HD wide format convertible monitor perfect for a wide range of applications, embedded or exposed, that requires quality and reliability in high use environments. Versatile by design, this 21.5" wide monitor fits a variety of applications with the ability to withstand harsh conditions while retaining high performance levels. The IP65 rating coupled with an updated I/O selection for seamless integration and OSD controls built into the back housing create a user experience that is effortless and simplistic.

Featured Specifications

- Size: 21.5" TFT LCD
- Maximum Resolution: 1920 x 1080
- Contrast Ratio: 1000:1
- Aspect Ratio: 16:9
- Brightness: 250 nits (No Touch), 217 nits (P-CAP)
- View Angle: H:178°, V:178°
- Video Port: 1 x VGA (DB15), 1 x HDMI, 1x DP
- Warranty: 3 year

Specifications

Touch LCD Display

| | |
|------------------------|----------------------|
| Touch Screen | Projected Capacitive |
| Touch Points | 10 |
| Touch Screen Interface | USB-HID (Type B) |

I/O Ports

| | |
|-------------|--|
| Serial Port | 1 x RJ45 Remote OSD |
| USB Port | 1 x USB 2.0 (Type B) for Touch Interface |
| Video Port | 1 x VGA (DB15), 1 x HDMI, 1x DP |
| Audio Port | – |
| Power Input | 1 x 2.1 mm 12V DC Jac |

Physical Properties

| | |
|---------------------------|---|
| Power Supply | Max. 60W (12V, 5A) External Power Adaptor |
| Speaker | – |
| Housing Color | Black |
| Construction | Glass, SECC Metal, Plastic (ABS) |
| Compliance | Front Panel IP65 Compliant, Rear IPX1 |
| Dimensions (W x H x D) mm | 517.4 x 313.3 x 46.0 mm |
| Net Weight (kg) | 4.4 kg |
| Gross Weight (kg) | 6.8 kg |
| Carton (W x H x D) mm | 610 x 405 x 160 mm |
| VESA | 100 x 100 mm |
| Ball Drop | – |

Safety

| | |
|----------------|--|
| Certifications | CE/FCC/UL(62368)/TUV (60950)/CCC/BSMI/LVD(65950) |
|----------------|--|

Environment

| | |
|-----------------------|--|
| Operating Temperature | 0° C ~ 40° C, 20% ~ 80% RH. Non-Condensing |
| Storage Temperature | -20° C ~ 60° C, 10% ~ 90% RH. Non-Condensing |

Optional Peripheral

| | |
|------------------|-----------------------------|
| Industrial Stand | IS-000-A1 (Sold Separately) |
| Remote OSD | Rem45-A1 (Sold Separately) |



www.MicroTouch.com | us.orders@microtouch.com

TES America, LLC | 215 Central Avenue, Holland, MI 49423 | (616) 786-5353

The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by TES America, LLC. standard terms and conditions of sale. Products are subject to availability. Copyright © 2021 TES America, LLC. All rights reserved. MT21-1019