

SK-320P-P1

32" PCAP Touch Monitor



Description

Introducing the SK-320P-P1 Multi-Touch Display. This display offers a smartphone-like touch experience in a commercial display specially engineered for 24/7 operation. With features like high-performance projected capacitive multi-touch technology, a sophisticated bezel-free design for a truly uncompromised touch experience, an active thermal management system to ensure cool-to-the-touch performance in all display orientations, Full HD 1920 x 1080 resolution, this display delivers a premium interactive experience to teach, inspire, inform, and sell..

Featured Specifications

- Size: 32"
- Maximum Resolution: 1920 x 1080
- Brightness: 500 nits (No Touch), 450 nits (P-CAP)
- View Angle: H:178°, V:178°
- Video Port: 1 x HDMI(HDCP), 1 x VGA, 1 x DVI, 1 x DP(HDCP)

Specifications

Touch LCD Display

Touch Screen	Projected Capacitive
Touch Points	80 with Palm Rejection 10ms response (up to 20 touches)
Touch Screen Interface	USB
Screen Treatment	Anti-Glare

I/O Ports

Serial Port	–
USB Port	1 x USB 2.0 (Type B) for Touch Interface (USB-HID)
Video Port	1 x HDMI (HDCP), 1 x VGA, 1 x DVI, 1 x DP (HDCP)
Audio	Audio Input, 5W + 5W @ 8Ω (1 x In/Out)
Power Input	Internal, 110/220 VAC

Physical Properties

Power Supply	AC Input 100~240Vac, 50~60Hz
Housing Color	Black
Dimensions (W x H x D) mm	759 x 454 x 66
Net Weight (kg)	12.7
Gross Weight (kg)	17.5
Carton (W x H x D) mm	850 x 683 x 211
VESA	200×200

Safety

EU Energy Efficiency Class	B
----------------------------	---

Environment

Operating Temperature	0° C ~ 40° C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-10° C ~ 60° C, 20% ~ 90% RH. Non-Condensing

Optional Peripheral

N/A

