

# SK-320P-P1

## 32" PCAP Touch Monitor



### Description

Introducing the SK-320P-P1 Multi-Touch Display. This display offers a smartphone-like touch experience in a commercial display specially engineered for 24/7 operation. With features like high-performance projected capacitive multi-touch technology, a sophisticated bezel-free design for a truly uncompromised touch experience, an active thermal management system to ensure cool-to-the-touch performance in all display orientations, Full HD 1920 x 1080 resolution, this display delivers a premium interactive experience to teach, inspire, inform, and sell..

### Featured Specifications

- Size: 32"
- Maximum Resolution: 1920 x 1080
- Contrast Ratio: 3000:1
- Aspect Ratio: 16:9
- Brightness: 500 nits (No Touch), 450 nits (P-CAP)
- View Angle: H: 178°, V: 178°
- Video Port: 1 x HDMI (HDCP), 1 x VGA, 1 x DVI, 1 x DP (HDCP)
- Warranty: 3 year



# Specifications

## Touch LCD Display

|                        |   |
|------------------------|---|
| Touch Screen           | Projected Capacitive                                      |
| Touch Points           | 80 with Palm Rejection   10ms response (up to 20 touches) |
| Touch Screen Interface | USB   |
| Screen Treatment       | Anti-Glare  |

## I/O Ports

|             |  |
|-------------|--|
| Serial Port | –  |
| USB Port    | 1 x USB 2.0 (Type B) for Touch Interface (USB-HID) |
| Video Port  | 1 x HDMI (HDCP), 1 x VGA, 1 x DVI, 1 x DP (HDCP)   |
| Audio       | Audio Input, 5W + 5W @ 8Ω (1 x In/Out)             |
| Power Input | Internal, 110/220 VAC                              |

## Physical Properties

|                           |                              |
|---------------------------|------------------------------|
| Power Supply              | AC Input 100~240Vac, 50~60Hz |
| Housing Color             | Black                        |
| Dimensions (W x H x D) mm | 759 x 454 x 66               |
| Net Weight (kg)           | 12.7                         |
| Gross Weight (kg)         | 17.5                         |
| Carton (W x H x D) mm     | 850 x 683 x 211              |
| VESA                      | 200×200                      |

## Safety

|                            |   |
|----------------------------|---|
| EU Energy Efficiency Class | B |
|----------------------------|---|

## Environment

|                       |  |
|-----------------------|--|
| Operating Temperature | 0° C ~ 40° C, 20% ~ 80% RH. Non-Condensing   |
| Storage Temperature   | -10° C ~ 60° C, 20% ~ 90% RH. Non-Condensing |

## Optional Peripheral

|     |
|-----|
| N/A |
|-----|



[www.MicroTouch.com](http://www.MicroTouch.com) | [us.orders@microtouch.com](mailto:us.orders@microtouch.com)  
TES America, LLC | 215 Central Avenue, Holland, MI 49423 | (616) 786-5353

The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by TES America, LLC. standard terms and conditions of sale. Products are subject to availability. Copyright © 2021 TES America, LLC. All rights reserved. MT21-1020