

Specifications

Touch LCD Display

Touch Screen	Projected Capacitive
Touch Points	10
Touch Screen Interface	USB-HID (Type B)

I/O Ports

Serial Port	–
USB Port	1 x USB 2.0 (Type B) for Touch Interface (USB-HID)
Video Port	1 x VGA (DB15), 1 x DP, 1 x HDMI
Audio Port	1x Audio Line-in
Power Input	1 x 2.1 mm 12V DC Jack

Physical Properties

Power Supply	50W (12V, 4.16A) External Power Adaptor
Speaker	2 x 1.5W
Housing Color	Silver
Construction	Aluminum Die-casting, Plastic (ABS), Glass, SECC Metal
Compliance	IP65 Compliant, Rear IPX1
Dimensions (W x H x D) mm	356.1 x 321.9 x 201.4 mm
Net Weight (kg)	4.2 kg
Gross Weight (kg)	6.8 kg
Carton (W x H x D) mm	470 x 395 x 293 mm
VESA	100 x 100 mm
Ball Drop	–

Safety

Certifications	CE(Class A)/FCC(Class A)/LVD(62368)
----------------	-------------------------------------

Environment

Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH. Non-Condensing

Optional Peripheral

MSR	MSR-150-A1
VFD with Camera	VFDC-150-A1
VFD	VFD-150-A1
LCM	LCM-150-A1



www.MicroTouch.com | us.orders@microtouch.com

MicroTouch Interactive, Inc.
200 East Broadway Avenue, Maryville, TN 37804 | (616) 786-5353

The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by MicroTouch Interactive, Inc. standard terms and conditions of sale. Products are subject to availability. Copyright © 2025 MicroTouch Interactive, Inc. All rights reserved. MT21-1021 - 032425