

# Specifications

## Touch LCD Display

Touch Screen	Projected Capacitive
Touch Points	10
Touch Screen Interface	USB-C

## I/O Ports

Serial Port	1 x RJ11 (for Remote Key)
USB Port	1 x USB Type C (Alt Mode for DP video support)
Video Port	1 x VGA, 1 x DP, 1 x HDMI (up to 1920 x 1080 @60Hz)
Audio Port	1 x Audio-Input (3.5 mm Mini-Jack)
Power Input	1 x DC In 12V Jack Power Input

## Physical Properties

Power Supply	Max. 60W (12V, 5A) External Power Adaptor
Speaker	2 x 2W
Housing Color	Black
Construction	Glass, Plastic (ABS), SECC Metal
Compliance	-
Dimensions (W x H x D) mm	369.1 x 223.7 x 27.2 mm (monitor only)
Net Weight (kg)	1.805 kg (monitor only)
Gross Weight (kg)	2.80 kg (monitor only)
Carton (W x H x D) mm	455 x 315 x 150 mm (monitor only)
VESA	100 x 100 mm
Ball Drop	-

## Safety

Certifications	CE, FCC, LVD, RoHS
----------------	--------------------

## Environment

Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH. Non-Condensing

## Optional Peripheral

Camera	Cam-A1 (Sold Separately)
MSR	MSR-A1 (Sold Separately)
15.6" Slim Stand	SS-156-A1 (Sold Separately)



[www.MicroTouch.com](http://www.MicroTouch.com) | [us.orders@microtouch.com](mailto:us.orders@microtouch.com)

MicroTouch Interactive, Inc.  
200 East Broadway Avenue, Maryville, TN 37804 | (616) 786-5353

The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by MicroTouch Interactive, Inc. standard terms and conditions of sale. Products are subject to availability. Copyright © 2025 MicroTouch Interactive, Inc. All rights reserved. MT21-1024 - 032425