

IC-215P-AW1-W10

21.5" PCAP Touch Computer




Stand sold separately
Part #SS-215-A1

Description

The IC-215P-AW1-W10 is equipped with a Celeron® J1900 processor, standard with 8GB DDR3L memory and 128GB storage. Combining computing performance, support of Microsoft legacy OS versions, and enterprise control with our industry leading touch experience enables an effortless and reliable solution for a variety of applications. Designed with an ultra-modern, slim aesthetic, versatile I/O selections and edgeless touch brings to life a true value-add experience for customers. It offers flexibility from POS to an exposed kiosk, self-service to point-of-information, and landscape to portrait. The IC-215P-AW1-W10 offers peripherals, MSR and Camera Module Kit, to support a wide range of applications, making it a perfect form, fit and function solution. Stand is sold separately (part #SS-215-A1).

Featured Specifications

- Size: 21.5" TFT LCD
- Processor: Celeron® J1900 (2.0 GHz, 2M Cache)
- Maximum Resolution: 1920 x 1080
- Contrast Ratio: 1000:1
- Aspect Ratio: 16:9
- Brightness: 250 nits (No Touch), 225 nits (P-CAP)
- View Angle: H: 178°, V: 178°
- Video Port: 1 x VGA
- Warranty: 3 year



Specifications

System Configuration

Processor	Celeron® J1900 (2.0 GHz, 2M Cache)
GPU	Integrated Intel® HD Graphic Engine
System Memory	8GB So-DIMM DDR3L, 1333 MHz
Storage Device	128GB SSD
Wi-Fi & Bluetooth	802.11 a/b/g/n/ac, Bluetooth 4.2 (Support BLE)

Touch LCD Display

Touch Screen	Projected Capacitive Touch, 10 points
Brightness	250 nits (No Touch), 225 nits (P-CAP)
Contrast Ratio	1000:1
Aspect Ratio	16:9
View Angle	H:178°, V:178°
Display Surface	7H Hardness Durable Glass

I/O Ports

Serial Port	2 x RS232 (RJ50 Type)
USB Port	4 x USB 2.0 Type A
LAN Port	1 x RJ45 Giga LAN
Video Port	1 x VGA
Audio Port	1 x Line Out
DC Output	1 x DC Out 12V/1A 2 Pin
Power Input	1 x DC in 12V/5A 4 pin, via 60W External Power Adapter

Operating System Support

OS	Windows® 7 & 10
----	-----------------

Physical Properties

Speaker	2 x 2W
Material	Plastic, Glass, SECC Metal
Housing Color	Dark Gray
Dimensions (W x H x D) mm	510.96 mm x 322.28 x 172.98 mm
Net Weight (kg)	6.77 kg
Gross Weight (kg)	9.79 kg
Carton (W x H x D) mm	615 mm x 450 mm x 330 mm
VESA	100 mm x 100 mm

Specifications

Safety

Certifications	CE, FCC, LVD, UL, CCC, BSMI, RoHS
----------------	-----------------------------------

Environment

Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing
-----------------------	--

Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH. Non-Condensing
---------------------	--

Optional Peripheral

MSR	MSR-215-A1 (Sold Separately)
-----	------------------------------

Camera	CAM-000-A1 (Sold Separately)
--------	------------------------------

Stand	SS-215-A1 (Sold Separately)
-------	-----------------------------



www.MicroTouch.com | us.orders@microtouch.com
TES America, LLC | 215 Central Avenue, Holland, MI 49423 | (616) 786-5353

The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by TES America, LLC. standard terms and conditions of sale. Products are subject to availability. Copyright © 2021 TES America, LLC. All rights reserved. MT21-1045