

LCM-150-A1

Peripheral Display



Description

The LCM-150-Al is an optional peripheral designed specifically for the DT-150P-Al model. This 2×20 LCM display allows customers to view their order total, line item amount, tax, discounts, and more during the checkout process. Adjustable display for optimal viewing angle.

Warranty: 3 year



Specifications

Display Method	STN LCD
Resolution	320 (W) x 32 (H) Dots
Number of Characters	20 columns x 2 lines
Character Dot Matrix (Font Resolution)	16 x 16 Dots
Dot Size	0.35 (W) x 0.6 (H) mm
Viewing Direction	12 O'clock
Brightness	400 cd/m2
Character Type	Alphanumeric and Compound (2-Bytes) Words
Character Size	10 (H) mm x 6 (W) mm
Internal ROM Download Characters	9 Characters
Viewing Area	123 (W) x 22.2 (D) mm
Module Kit Dimensions	139 (W) x 35 (H) x 11.8 (D) mm
Viewing Angle	Max. 90°
Horizontal Rotation	Max. 355°
Weight (Module Kit Only)	Approx. 70 grams
Commands Mode	Ultimate (Epson command compatible), LD540, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Language Support	Compound (2-Bytes) Words: Traditional Chinese, Simplified Chinese, Korean, Arabic, Persian
	Alphanumeric: US English, Int'l English, Turkish, Bosnia, Croatian, Czech, Danish, Dutch, Estonian, Faroese, Finnish, Flemish, French, Fr Canadian, German, Greek, Hebrew, Hungarian, Icelandic, Indonesian, Irish, Italian, Katakana, Latvian, Lithuanian, Norwegian, Polish, Portuguese, Romanian, Russian, Slovene, Slovak, Spanish, Swedish
Interface	RS-232 (serial) / USB in 5V only
Connection Baud Rate	Direct connection 9600 or 19,200 bps
Reliability MTBF	30,000 hours
Power Consumption	5~12 VDC
Agency Approvals	FCC, CE
Weight (net)	0.168 kg
Housing Color	Silver
What's Included	2×20 LCM

