

MSR-150-A1

Peripheral



Description

The MSR-150-A1 is an optional peripheral designed specifically for the DT-150P-A1 touch monitor. This MSR is a three track, bi-directional, encrypted solution for a variety of application use-cases.

Warranty: 3 year



Specifications

Swipe Speed	ISO standard card: 5-55, Jitter: 5-50, Low Amplitude: 5-50
Swipe Direction	Bi-directional
Number of Tracks	Track 1 & 3 210 bpi, Track 2 75/210 bpi
Power Supply	+5VDC, +/-5%
Power Consumption (Typical)	50 mA Max.
Interface	USB-A
Supported Formats	ISO 7811, CA old DMV, AAMVA, Tradeshow card, Read high or low coercivity magnetic stripes (300-4000oe)
Supported Emulation Modes	Keyboard Emulation Mode, Uniform Defined HID Device Mode (HID MSR)
Card Width	3.375 x 2.125 in.
Supported Operating Systems	Windows 10 / Android
Mounting	Directly to DT-150P-A1
Dimensions (H x W x D)	255 x 220 x 388 mm
Weight (gross)	2.11 kg
Weight (net)	0.09 kg
Housing Color	White
What's Included	Bi-Directional MSR



www.MicroTouch.com | us.orders@microtouch.com

TES America, LLC | 215 Central Avenue, Holland, MI 49423 | (616) 786-5353

The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by TES America, LLC. standard terms and conditions of sale. Products are subject to availability. Copyright © 2024 TES America, LLC. All rights reserved. MT24-1178