

# MSR-215-A1

## Peripheral

---



### Description

The MSR-215-A1 is an optional peripheral designed specifically for the DT-215P-A1 and IC-215P-AA2 models. This MSR is a three track, bi-directional, encrypted solution for a variety of application use-cases.

Warranty: 3 year



# Specifications

Swipe Speed	ISO standard card: 5-55, Jitter: 5-50, Low Amplitude: 5-50
Swipe Direction	Bi-directional
Number of Tracks	Track 1 & 3 210 bpi, Track 2 75/210 bpi
Power Supply	+5VDC, +/-5%
Power Consumption (Typical)	50 mA max.
Interface	USB
Supported Formats	ISO 7811, CA old DMV, AAMVA, Tradeshow Card, Read High or Low Coercivity Magnetic Stripes (300-4000oe)
Supported Emulation Modes	Keyboard Emulation Mode, Uniform Defined HID Device Mode (HID MSR)
Card Width	3.375 x 2.125 in.
Supported Operating Systems	Windows 10 / Android
Mounting	Directly to DT-215P-A1
Dimensions (H x W x D)	245 x 300 x 385 mm
Weight (gross)	2.086 kg
Weight (net)	0.078
Housing Color	Black
What's Included	MSR, 2 Screws



[www.MicroTouch.com](http://www.MicroTouch.com) | [us.orders@microtouch.com](mailto:us.orders@microtouch.com)

TES America, LLC | 215 Central Avenue, Holland, MI 49423 | (616) 786-5353

The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by TES America, LLC. standard terms and conditions of sale. Products are subject to availability. Copyright © 2024 TES America, LLC. All rights reserved. MT24-1180