

2D-LMH-A1

Barcode Scanner



Description

The 2D-LMH-A1 Barcode scanner is a newly designed, state of the art 2D Barcode Scanner. It's sleek, compact, and ultra-modern design aesthetic makes it extremely reliable and convenient for customer work environments. The 2D-LMH-A1 operates in landscape mode. It is extremely motion tolerant with the ability to reach up to 120 fps with the capability to reach up to 6 m/s with its image capture rate. The advanced feature set of this next generation scanner creates a convenient and hassle-free solution for customer scanning applications.

Warranty: 3 year



Specifications

Housing Color	Black
Compatibility	All-in-One Touch Computer Series with Android & Windows OS
Barcode Engine	Honeywell N4680
Standard Configuration	Presentation Mode
Supported Terminal Modes	USB HID Keyboard Mode, USB Serial Model, HID POS Mode
Resolution	640×480
Illumination & Aiming	3000K LED & 630nm LED
Ideal Scan Distance	36 mm to 747 mm (Performance may be impacted by barcode quality and environmental conditions)
Supported Symbols	1D : Codabar, Code 11, Code 128, Code 2 of 5, Code 39, Code 93 and 93i, EAN/JAN-13, EAN/JAN 8, IATA Code 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI, GS1 Databar, UPC-A, UPC E, UPC-A/EAN-13 with Extended Coupon Code, Coupon GS1 Code 32(PARAF), EAN-UCC Emulation, GS1 Data Bar 2D : Codablock A, Codablock F, PDF417, MicroPDF417, Aztec Code, Data Matrix, Maxi Code, QR Code, Chinese Sensible(Han Xin) Code, DotCode, Grid Matrix
Postal Codes	Australian Post, British Post, Canadian Post, China Post, Japanese Post, Korea Post, Netherlands Post, Planet Code, Postnet
Viewing Angle	40° horizontal × 30° vertical
Audio	Yes
Gross Weight	0.104 Kg
Net Weight	0.049 Kg
Dimensions	79.6 x 56.6 x 35.4 mm
Operating Temperature	-30°C to 60°C
Storage Temperature	-40°C to 70°C
Humidity	0% to 95% relative humidity, non-condensing, at 60°C
What's Included	2 screws



www.MicroTouch.com | us.orders@microtouch.com

TES America, LLC | 215 Central Avenue, Holland, MI 49423 | (616) 786-5353

The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by TES America, LLC. standard terms and conditions of sale. Products are subject to availability. Copyright © 2024 TES America, LLC. All rights reserved. MT24-1170