

MA-CAM-A1

Camera



Description

The new Mach Camera, MA-CAM-A1, is an optional camera peripheral specifically designed to seamlessly integrate into the new Mach series. Equipped with the ability to plug in to any of the 4 sides of the Mach desktop touch displays with a high-reliable USB-C port, customers have more versatility and flexibility than ever before. Featuring full HD video, an 8 MP camera, and 8.0M sensor resolution, this high-definition camera matches the Mach sleek aesthetics and simplifies the complete solution.

Specifications

Resolution	3264 x 2448 (8M) @15fps, FHD 1920 x 1080 @30fps
Compliance	RoHS, REACH, CE, FCC, ISED

MODULE SPECIFICATIONS

Dimensions	111.3 x 68.1 x 18 (mm)
Weight	0.06 Kg

LENS SPECIFICATION

Lens Composition	4 Plastic + IR Filter (5E)
Diagonal(D)	75°
Horizontal(H)	63°
Vertical(V)	49°
F No.	2.2 ±5%
Focus Mode	Fixed Focus (FF)
Focus Range	10cm~ ∞

IMAGE SENSOR SPECIFICATION

CMOS Image Sensor	1/4" 8M CMOS Sensor
Active Array Size	3264 (H) x 2448 (V)
Pixel Size	1.12 um x 1.12 um
Image Format Output	YUV, MJPEG

ELECTRICAL SPECIFICATION

Input Voltage	USB 5.0V ±250mV
Temperature Range	0° ~ 55°

OTHER

Housing Color	Black
What's Included	Mylar pads x 2 ; screw x 2



www.MicroTouch.com | us.orders@microtouch.com

MicroTouch Interactive, Inc.
200 East Broadway Avenue, Maryville, TN 37804 | (616) 786-5353

The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by MicroTouch Interactive, Inc. standard terms and conditions of sale. Products are subject to availability. Copyright © 2025 MicroTouch Interactive, Inc. All rights reserved. MT24-1165 - 032125